



EMFLEX[®]

Ductwork Rubber Hangers

N. Minikin & Sons Limited

Spa House, Hookstone Park, Harrogate, North Yorkshire, HG2 7DB

Email: enquiries@minikins.co.uk Web: www.minikins.co.uk

Tel: 01423 889845 Fax: 01423 880724



Ductwork Rubber Hangers

EMFLEX ductwork rubber hangers are an economic solution for isolating building services ductwork from the structure.

They are available for load ratings up to a maximum of 200kg per hanger. The rubber turret element will compress proportionally to the actual load applied; ie full compression will be achieved when a load is applied which is equal to the load rating.



TYPE HR

A moulded rubber turret hanger consisting of a colour coded rubber element fitted in an aluminium hollow section housing. Fixing holes allow for installation in standard stud.

TYPE	HEIGHT	WIDTH	LENGTH	FIXING
HR-A 25Kg Red	100mm	50mm	50mm	M8
HR-A 60Kg Yellow	100mm	50mm	50mm	M8
HR-A 85Kg Blue	100mm	50mm	50mm	M8
HR-B 100Kg Red	150mm	80mm	100mm	M12
HR-B 200Kg Yellow	150mm	80mm	100mm	M12
HR-B 300Kg Blue	150mm	80mm	100mm	M12
HR-C 450Kg Yellow	200mm	100mm	100mm	M16
HR-C 600Kg Blue	200mm	100mm	100mm	M16