



**EMFLEX<sup>®</sup>**

**Spring Hangers**

**N. Minikin & Sons Limited**

Spa House, Hookstone Park, Harrogate, North Yorkshire, HG2 7DB

Email: [enquiries@minikins.co.uk](mailto:enquiries@minikins.co.uk) Web: [www.minikins.co.uk](http://www.minikins.co.uk)

Tel: 01423 889845 Fax: 01423 880724



# Spring Hangers

EMFLEX spring hangers are used to support pipework from above, to minimise the transmission of noise and vibration to the building structure.

They may be suspended from drop rods above or bolted directly to the soffit or slab.

Available with a standard deflection of 25mm. The spring will compress proportionally to the actual load applied; ie full compression of 25mm will be achieved when a load is applied which is equal to the load rating.

## TYPE HS

An open spring hanger consisting of a colour coded steel spring and rubber isolating end caps. Fitted in a plated steel hanger box. Complete with fixing stud and connector for fixing lower drop rod.



TYPE	HEIGHT	HOLE DIAMETER	WIDTH	LENGTH	FIXING
HS-A 25Kg Yellow	100mm	9mm	50mm	50mm	M8
HS-A 50Kg Green	100mm	9mm	50mm	50mm	M8
HS-A 75Kg Blue	100mm	9mm	50mm	50mm	M8
HS-A 100Kg Red	100mm	9mm	50mm	50mm	M8
HS-B 50Kg Black	150mm	14mm	80mm	100mm	M12
HS-B 75Kg Orange	150mm	14mm	80mm	100mm	M12
HS-B 100Kg White	150mm	14mm	80mm	100mm	M12
HS-B 150Kg Green	150mm	14mm	80mm	100mm	M12
HS-B 200Kg Yellow	150mm	14mm	80mm	100mm	M12
HS-B 300Kg Blue	150mm	14mm	80mm	100mm	M12
HS-B 400Kg Purple	150mm	14mm	80mm	100mm	M12
HS-B 500Kg Red	150mm	14mm	80mm	100mm	M12
HS-C 400Kg Black	200mm	18mm	100mm	100mm	M16
HS-C 600Kg Yellow	200mm	18mm	100mm	100mm	M16
HS-C 800Kg Green	200mm	18mm	100mm	100mm	M16
HS-C 1000Kg Blue	200mm	18mm	100mm	100mm	M16
HS-C 1200Kg Red	200mm	18mm	100mm	100mm	M16

High deflection (50mm) units are available.  
Add suffix 'H' to the model type code. (e.g. HS-A-H).  
Dimensions are available on request.

### Note:

The fixing stud size is based on safe working loads stated in BS3974.